

**Amendments to the Claims:**

The listing of claims will replace all prior versions, and listings, of claims in the application:

**Listing of Claims:**

1. (Original) An electro-magnetic field analysis program of an electric rotating machine for a computer to execute:

the first electro-magnetic field analysis procedure of analyzing the electro-magnetic field in an analysis space based on the first boundary condition in terms of an electro-magnetic variable assigned to the first specific portion in the analysis space;

a development procedure of developing the electro-magnetic variable at the second specific portion in the analytic space, obtained in the first electro-magnetic field analysis procedure, into each higher-harmonic component;

the second boundary condition setting procedure of assigning an electro-magnetic variable in terms of at least one of the higher-harmonic components, developed from the above electro-magnetic variable, to the second specific portion as the second boundary condition; and

a procedure of analyzing the electro-magnetic field of the analysis space based on the first and second boundary conditions.

2. (Original) An electro-magnetic field analysis program of an electric rotating machine according to claim 1, wherein, in the development procedure, the electro-magnetic variable is developed into each higher-harmonic component in terms of spatial distribution.

3. (Original) An electro-magnetic field analysis program of an electric rotating machine according to claim 1, wherein, in the development procedure, the electro-magnetic variable is developed into each higher-harmonic component in terms of time distribution.

4. (Original) An electro-magnetic field analysis program of an electric rotating machine according to claim 1, wherein the electro-magnetic variable is potential or magneto-motive force.

5. (Original) An electro-magnetic field analysis program of an electric rotating machine according to claim 1, wherein a storage procedure of storing the permeability distribution of the analysis space is included before the first electro-magnetic field analysis procedure, and, in the first and second electro-magnetic field analysis procedures, the electro-magnetic field analysis of the analysis space is based on the permeability distribution stored in the storage procedure.

6. (Original) An electro-magnetic field analysis program of an electric rotating machine according to claim 1, wherein the analysis space comprises an analysis space corresponding to the stator and an analysis space corresponding to the rotor, and the second specific portion is the boundary between the analysis space corresponding to the stator and analysis space corresponding to the rotor.

7. (Original) An electro-magnetic field analysis program of an electric rotating machine for a computer to execute:

- a total electro-magnetic field analysis procedure of analyzing the total electro-magnetic field of the electric rotating machine by assigning a boundary condition to the outer boundary surface of the analysis space and applying a magneto-motive force by current or magnetic force;

- a procedure of storing the permeability distribution in the magnetic substance obtained in the total electro-magnetic field analysis procedure;

- a procedure of developing the potential, which describes the electro-magnetic field distribution on the sliding surface between the rotor and stator obtained in the total electro-magnetic field analysis, into multiple higher-harmonic components that have some distribution in the axial direction and a

constant or periodic distribution in the direction of rotation;

a procedure of accomplishing a linear electro-magnetic field analysis in each rotor space including the rotor and stator space including the stator, wherein the same boundary condition as in the total electro-magnetic field analysis procedure is assigned, a Dirichlet's condition is assigned to the sliding surface, the stored permeability distribution is assigned and fixed to the whole analysis space, and current or magnetic force applied in the total electro-magnetic field analysis procedure is applied; and

a procedure of accomplishing a linear electro-magnetic field analysis in each rotor space including the rotor and stator space including the stator, wherein the same boundary condition as in the total electro-magnetic field analysis procedure is assigned, the higher-harmonic components are assigned, one after another, to the sliding surface as the boundary condition, the permeability distribution is assigned to the whole magnetic substance, and current or magnetic force is set zero.

8. (Original) An electro-magnetic field analysis program of an electric rotating machine according to claim 7, wherein, in the case of analyzing a three-dimensional rotating structure, in the procedure of analyzing the electro-magnetic field of the electric rotating machine by assigning a boundary condition to the outer boundary surface of the analysis space and applying a magneto-motive force by current or magnetic force, a procedure of converting a potential obtained under a gage-free or partially gage-free condition into a potential meeting the gage condition is executed before the procedure of developing the potential into the higher-harmonic components.

9. (Original) An electro-magnetic field analysis program of an electric rotating machine according to claim 7 or 8, wherein a procedure of displaying the electro-magnetic field distribution, obtained through individual analysis in the above-mentioned each rotor space and stator space, individually by each assigned boundary condition.

10. (Original) An electro-magnetic field analysis program of an electric rotating machine for a computer to execute:

a total electro-magnetic field analysis procedure of analyzing the total electro-magnetic field of the electric rotating machine in a series of time steps by assigning a boundary condition to the outer boundary surface of the analysis space and applying a magneto-motive force by current or magnetic force;

a procedure of storing the permeability distribution in the magnetic substance in a series of time steps obtained in the total electro-magnetic field analysis procedure;

a procedure of developing and storing the potential, which describes the electro-magnetic field distribution on the sliding surface between the rotor and stator obtained in the total electro-magnetic field analysis, into multiple higher-harmonic components that have some distribution in the axial direction and a constant or periodic distribution in the direction of rotation;

a procedure of abstracting the time and spatial higher-harmonic components by developing the multiple higher-harmonic components which, obtained in the above analysis in a series of time steps, have a constant or periodic distribution in the direction of rotation into higher-harmonic components along the time axis;

a procedure of accomplishing a linear electro-magnetic field analysis in each rotor space including the rotor and stator space including the stator, wherein the same boundary condition as in the total electro-magnetic field analysis procedure is assigned, a Dirichlet's condition is assigned to the sliding surface, current or magnetic force applied in the total electro-magnetic field analysis procedure is applied, and the permeability distribution in the magnetic substance in a series of time steps is assigned in each time step; and

a procedure of accomplishing a linear electro-magnetic field analysis in each rotor space including the rotor and stator space including the stator, wherein the same boundary condition as in the total electro-magnetic field analysis procedure is assigned, the time and spatial higher-harmonic

components are assigned, one after another, to the sliding surface as the boundary condition, the permeability distribution in the magnetic substance in a series of time steps is assigned and fixed in each time step, and current or magnetic force is set zero.

11. (Currently Amended) An electro-magnetic field analysis program of an electric rotating ~~machin~~ machine according to claim 10, wherein, in the case of analyzing a three-dimensional rotating structure, in the procedure of analyzing the electro-magnetic field of the electric rotating machine by assigning a boundary condition to the outer boundary surface of the analysis space and applying a magneto-motive force by current or magnetic force, a procedure of converting a potential obtained under a gage-free or partially gage-free condition into a potential meeting the gage condition is executed before the procedure of developing the potential into the higher-harmonic components.

12. (Previously Presented) An electro-magnetic field analysis program of an electric rotating machine according to claim 10, wherein a procedure of displaying the electro-magnetic field distribution, obtained through individual analysis in the above-mentioned each rotor space and stator space, individually by each assigned boundary condition.

13. (Previously Presented) An electro-magnetic field analysis program of an electric rotating machine according to claim 11, wherein a procedure of displaying the electro-magnetic field distribution, obtained through individual analysis in the above-mentioned each rotor space and stator space, individually by each assigned boundary condition.